

DESCRIPTION

SPECTACLE LENS MANUFACTURING METHOD AND SPECTACLE LENS
SUPPLY SYSTEM

5

TECHNICAL FIELD

This invention relates to a supply system equipped with a lens design function, with which a spectacle lens with good appearance and optical performance can be obtained even when the difference in prescription, such as the diopter, between the left and right eyes is over a specific amount, and furthermore with which optical performance can be taken into account when the wearer changes his or her prescription and new spectacles are produced, or when the eyewear history of a customer is updated.

BACKGROUND ART

There are already known systems for the online ordering of spectacle lenses (see Japanese Patent No. 2,982,991, for instance). With this conventional system, a computer is set up on the side where the spectacle lenses are ordered, and a manufacturer-side computer is connected to this order-side computer so as to allow the exchange of information, with this computer executing order receipt processing such as obtaining lens design data on the basis of order information

such as a lens prescription transmitted from the order-side computer. The order-side computer and the manufacturer-side computer perform computational processing according to specific input operations, and perform the processing
5 necessary for placing and taking orders for spectacle lenses while exchanging information with each other.

In prescribing spectacle lenses that correct the vision of a patient's eyes, lenses of the same refractive power (diopter) are prescribed when the left and right eyes both
10 have the same visual acuity, so the curvature of the first refractive surface and the second refractive surface is also the same, and the optical performance, such as astigmatism, curvature of field, and distortion, is also the same. If the visual acuity of the left and right eyes is not the same,
15 however, lenses having different refractive power (diopter) will of course be prescribed.

According to Tscherning's ellipse, which Tscherning discovered as a geometric solution for eliminating astigmatism of a spectacle lens, the optimal base curve for
20 eliminating astigmatism (the refractive power of the first refractive surface) varies. Consequently, if the visual acuity differs between the left and right eyes, the base curve of the left and right lenses must also be different according to Tscherning's ellipse.

25 Therefore, when lenses are designed according to Tscherning's ellipse, if there is a great difference in

visual acuity between the left and right eyes as above, the left and right base curves will also be markedly different.

This means that the curved surface shape of the left and right spectacle lenses looks very unbalanced when the spectacles are viewed from the outside. Consequently, although optical performance is good, the appearance is quite poor.

Furthermore, since the curved surface shape is different for each individual lens on the lens manufacturer side, another disadvantage is higher manufacturing costs.

Accordingly, the same base curve is sometimes used within a specific diopter range in order to lower the manufacturing costs. However, lenses manufactured by this method may have a base curve that is not exactly optimal, so a problem is that the optical performance is inevitably inferior.

Naturally, if the base curves are merely made the same on the left and right in order to improve the appearance, optical performance will be markedly deteriorated in some cases. Thus, if emphasis is placed on the optical performance of the lenses, the cost will be higher and there will be cases in which appearance suffers. On the other hand, the problem with improving the appearance is that the optical performance may suffer.

Also, juvenile myopia tends to increase over time up to a certain age, and this is accompanied by changes in the prescription values for the spectacle lenses. Some wearers,

however, are physiologically sensitive to changes in prescription values. That is, they experience severe discomfort when they wear lenses manufactured with a new prescription, and in some cases the body itself may be
5 affected. These symptoms may appear even in regular customers, although not pronounced.

Research conducted by the inventors seems to indicate the primary cause of this to be as follows.

When a lens prescription changes, lenses having a
10 curved surface shape and so forth that match this new prescription are newly designed and manufactured for supply to the customer. In this case, it is not uncommon for the newly designed and manufactured lenses that match the new prescription to have optical performance (astigmatism,
15 curvature of field, and distortion) that is different from the optical performance of the old lenses designed to match the old prescription.

It is believed that symptoms such as discomfort will most often appear if this difference in optical performance
20 goes beyond a certain level.

Thus, the difference in optical performance has been a serious problem, one that occurs due to a diopter difference in prescription lenses resulting from differences between the left and right eyes, or to a diopter difference between
25 new and old lenses.

Unfortunately, the physician who gives the prescription and the business placing the order (such as an optician) do

characterized in that when spectacle lens information, spectacle frame information, prescription values, layout information, processing instructions information, and other such processing condition data required for processing is transmitted by the order-side computer to the manufacturer-side computer, a lens design program installed on the manufacturer-side computer performs optical lens design tailored to the customer on the basis of the transmitted data for lens information so that the optical performance of the left and right lenses will be similar, and the lenses are manufactured according to this design.

The second means is the spectacle lens supply method according to the first means, wherein the lens design program further performs optical lens design that approximates the left and right base curves to each other.

The third means is the spectacle lens supply method according to the first means, wherein the optical performance consists of at least one of astigmatism, curvature of field, and distortion.

The fourth means is the spectacle lens supply method according to the first means, comprising the steps of:

selecting the left and right lenses from a lens design table prepared on the basis of prescription values when the lens design program approximates the optical performance of the left and right eyes to each other;

comparing the convex surface base curve difference between the selected left and right lenses; and

when this base curve difference is over a predetermined standard, performing lens redesign in which the convex surface curve of one lens is made to have an aspherical shape similar to that of the convex surface curve of the other lens so that the astigmatism is substantially the same.

The fifth means is the spectacle lens supply method according to the second means, wherein the optical lens design is such that the difference in convex surface base curves of the left and right spectacle lenses is no more than 1 D.

The sixth means is the spectacle lens supply method according to the second means, wherein a display means for comparing data including the lens shape before the curve matching and the prescription data for this lens, to data including the lens shape after the curve matching and the prescription data for this lens, is transferred to and displayed at the computer set up on the side where spectacle lens is ordered.

The seventh means is a spectacle lens supply system, comprising a computer set up on a spectacle lens order side and a manufacturer-side computer that is information exchangeably connected to this order-side computer and has a customer database including spectacle lens prescription data and lens design data.

in which the order-side computer and the manufacturer-side computer perform computations according to specific input operations and perform the processing required for the

taking and/or placing of orders for spectacle lenses while exchanging information with each other,

wherein the manufacturer-side computer has the function of performing lens design such that a customer will

5 experience substantially no discomfort originating in an optical performance difference when changing from old to new lenses, by selecting or producing new design data for a lens on the basis of customer spectacle lens processing condition data required for processing, such as spectacle lens
10 information, spectacle frame information, prescription values, layout information, and processing instructions information, when this data is transmitted from the order-side computer to the manufacturer-side computer, and making the optical performance of the new lenses produced with this
15 new design data approximate the optical performance of the old lenses produced with the old design data based on the old prescription values of the pre-registered customer database.

The eighth means is a spectacle lens supply system,
20 comprising a computer set up on a spectacle lens order side and a manufacturer-side computer that is information exchangeably connected to this order-side computer and has a customer database including spectacle lens prescription data and lens design data,

25 in which the order-side computer and the manufacturer-side computer perform computations according to specific input operations and perform the processing required for the

taking and placing of orders for spectacle lenses while exchanging information with each other.

wherein, when customer spectacle lens processing condition data required for processing, such as spectacle
5 lens information, spectacle frame information, prescription values, layout information, and processing instructions information, is transmitted from the order-side computer to the manufacturer-side computer, the manufacturer-side computer has the function of performing processing
10 comprising:

a step of checking whether there is any old prescription data for that customer;

a step of selecting or producing lens design data matching the new prescription values as lens design data for
15 the new prescription values if no old data for that customer exists in the manufacturer-side computer, and setting this data as the design data for producing the new lenses;

an optical performance comparison step in which, if there is old prescription data for the customer, the new
20 lens design data for the new prescription values is selected or produced, and the optical performance of the new lenses designed on the basis of the newly selected or produced new design data is compared to the optical performance of the old lenses designed with the old design data matching the
25 old prescription values; and

a step in which, when the results of comparing the optical performance as above indicate that the optical

performance difference is within a range such that the customer will experience substantially no discomfort originating in an optical performance difference when changing from old to new lenses, the selected or produced
5 new design data is set as the design data for producing the new lenses, and when said difference goes outside a range in which the customer will experience substantially no discomfort originating in an optical performance difference when changing from old to new lenses, new design data is
10 newly selected or produced for putting the optical performance difference within said range before returning to said optical performance comparison step and such processing is repeated until the optical performance difference is within said range.

15 The ninth means is the spectacle lens supply system according to the seventh or eighth means, wherein the newly determined new design data is registered for the first time or updated in the customer database.

20 The tenth means is the spectacle lens supply system according to the seventh or eighth means, wherein, when there is old prescription data for the customer, a step is provided for comparing the difference between the old and new prescription values, and if this difference is not over 0.5 D as the diopter difference, the new lens design data
25 for the new prescription values is selected or produced without performing the optical performance comparison step,

and this data is set as the design data for producing the new lenses.

The eleventh means is the spectacle lens supply system according to the seventh or eighth means, wherein the lens
5 design data is such that the difference in the curve of a first refractive surface of the left and right spectacle lenses is no more than 1 D.

The twelfth means is the spectacle lens supply system according to the seventh or eighth means, wherein the
10 optical performance is at least one of astigmatism, curvature of field, and distortion.

The thirteenth means is the spectacle lens supply system according to the seventh or eighth means, wherein the curvature of at least one of the first refractive surfaces
15 of the left and right spectacle lenses is selected such that this curved surface will be aspherical.

The fourteenth means is a method for manufacturing a spectacle lens, involving the design and manufacture of left and right spectacle lenses that make up a pair of spectacles
20 in which the prescription including diopter is different for the left and right eyes,

wherein, if there is more than a specific amount of difference in the prescription including diopter between the left and right eyes:

25 when the refractive surfaces in front of the left and right spectacle lenses are termed the first refractive surfaces and the refractive surfaces on the eye side are

termed the second refractive surfaces, in designing the curvature of the curved surfaces of the first and second refractive surfaces of the left and right spectacle lenses, the curvature of the first and second refractive surfaces of
5 at least one of the left and right spectacle lenses is selected so that the left and right spectacle lenses satisfy their respective prescription conditions including the diopter so that the difference in the curvature of the first refractive surfaces between the left and right spectacle
10 lenses falls within a specific range.

The fifteenth means is a method for manufacturing a spectacle lens, involving the design and manufacture of left and right spectacle lenses that make up a pair of spectacles in which the prescription including diopter is different for
15 the left and right eyes.

wherein, if there is more than a specific amount of difference in the prescription including diopter between the left and right eyes:

when the refractive surfaces in front of the left and
20 right spectacle lenses are termed the first refractive surfaces and the refractive surfaces on the eye side are termed the second refractive surfaces, in designing the curvature of the curved surfaces of the first and second refractive surfaces of the left and right spectacle lenses,
25 the curvature of the first and second refractive surfaces of at least one of the left and right spectacle lenses is selected so that the left and right spectacle lenses satisfy

their respective prescription conditions including the diop-
 ter, so that the optical performance of each lens falls
 within an acceptable range, and so that the difference in
 the curvature of the first refractive surfaces between the
 5 left and right spectacle lenses falls within a specific
 range.

The sixteenth means is the method for manufacturing a
 spectacle lens pertaining to the fourteenth or fifteenth
 means, wherein the difference in the diop-ter between the
 10 left and right eyes is at least 0.5 D when the diop-ter
 prescription out of said prescription including the diop-ter
 includes a positive diop-ter, the difference in the diop-ter
 between the left and right eyes is at least 1 D when the
 diop-ter prescription includes a negative diop-ter, and the
 15 difference in the curvature of the first refractive surfaces
 of the left and right spectacle lenses is no more than 1 D.

The seventeenth means is the method for manufacturing a
 spectacle lens pertaining to the fifteenth means, wherein
 the optical performance consists of one or more of
 20 astigmatism, curvature of field, and distortion.

The eighteenth means is the method for manufacturing a
 spectacle lens pertaining to the fifteenth means, wherein
 the curvature of one or both of the first refractive
 surfaces of the left and right spectacle lenses is selected
 25 such that this curved surface will be aspherical.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a diagram illustrating the simplified structure of the spectacle lens supply system pertaining to an embodiment;

5 Fig. 2 is a diagram illustrating the auto-entry screen on which the type of lens is specified;

Fig. 3 is a block diagram of a manufacturer-side computer;

Fig. 4 is a diagram illustrating an example of part of
10 the contents of a customer database;

Fig. 5 is a flow chart of the processing involved in taking an order;

Fig. 6 is a design table (lens data table) for a lens of -2.0 D spherical design;

15 Fig. 7 is a design table (lens data table) for a lens of -4.0 D spherical design;

Fig. 8 is an astigmatism diagram for -2.0 D;

Fig. 9 is an astigmatism diagram for -4.0 D;

Fig. 10 is an aberration diagram of a new prescription
20 lens (aspherical design -4.0 D) obtained by redesign;

Fig. 11 is a diagram illustrating the principle of a ray tracing method;

Fig. 12 is a design table (lens data table) for a lens of -2.0 D spherical design;

25 Fig. 13 is a design table (lens data table) for a lens of -4.0 D spherical design;

Fig. 14 is an astigmatism diagram for -2.0 D;

Fig. 15 is an astigmatism diagram for -4.0 D;

Fig. 16 is a table of the radius of curvature, etc., of a new prescription lens (aspherical design -4.0 D) obtained by redesign;

5 Fig. 17 is an astigmatism diagram for a lens produced from the design table in Fig. 16;

Fig. 18 is a design table for a lens with a spherical design;

10 Fig. 19 is a table of the radius of curvature, etc., of a lens obtained by redesign (-1.0 D);

Fig. 20 is an astigmatism diagram for a lens produced from the design values (-1.0 D) in the table in Fig. 18;

Fig. 21 is an astigmatism diagram for a lens produced from the design values (-3.0 D) in the table in Fig. 18;

15 Fig. 22 is an astigmatism diagram for a lens produced from the design values (-1.0 D) in the table in Fig. 19;

Fig. 23 is an example of a lens design table for a positive lens spherical design (+1.00 D, +3.00 D);

20 Fig. 24 consists of astigmatism diagrams for lenses produced by spherical design, with (a) illustrating the case for the left eye and (b) for the right eye;

Fig. 25 is a table of the radius of curvature, etc., of a lens after redesign;

25 Fig. 26 is an astigmatism diagram for a lens after redesign; and

Fig. 27 consists of diagrams illustrating the screen display of the curved surface shape of a lens before and after redesign.

5

BEST MODE FOR CARRYING OUT THE INVENTION

Fig. 1 is a diagram illustrating the simplified structure of the spectacle lens supply system pertaining to an embodiment, Fig. 2 is a diagram illustrating the auto-entry screen on which the type of lens is specified, Fig. 3 is a block diagram of a manufacturer-side computer, and Fig. 4 is a diagram illustrating an example of part of the contents of a customer database. The spectacle lens supply system pertaining to an embodiment of the present invention will now be described through reference to these drawings.

In Fig. 1, computers 11, 12, 13, 14, and 15 are installed as order-side terminal computers at optician offices A and B, an optometrist or ophthalmologist office C, and individuals D and E, respectively. These are connected to a manufacturer-side computer 2 via the Internet or a dedicated communications line. The order-side terminal computers 11, 12, 13, 14, and 15 are part of a system that allows orders for spectacle lenses to be placed by exchanging information with the manufacturer-side computer 2 according to the instructions on a screen. Specifically, information related to producing spectacles, such as prescription values, lens information, frame information,

and layout information, is transmitted as data to the manufacturer-side computer 2, and the order type (such as unmachined circular lens, beveled lens, or spectacles) is specified by following the instructions on the screen, the
5 result being that the data necessary for that order is supplied from the manufacturer-side computer 2 and the order processed.

Fig. 2 is a diagram illustrating the auto-entry screen used to specify the type of lens. As shown in the figure,
10 the type of lens is specified in section 61. That is, the manufacturer's product category code is inputted, which specifies the lens material, refractive index, coating, lens coloring, optical design of the lens surface, outside diameter, and so forth. When there is an inquiry, two types
15 of lens can be specified. The "type" in section 65 specifies whether the lens being ordered or inquired about is a lens that has already been beveled (HELP) or one that has yet to undergo edging or beveling. The "METS machining" in section 65 specifies machining so that the thickness of
20 the lens will be the minimum required, or specifies chamfering to smooth off the edges of negative lens, or polishing of this portion.

Whether or not "binocular vision balance design" will be performed is specified by input in section 62.
25 "Binocular vision balance design" includes, of course, having the left and right lenses satisfy the prescription conditions within the specified range, but also means

While not shown in the drawing, a software menu is displayed at the bottom of the auto-entry screen in Fig. 2. Displayed on the screen here are a send key for sending registered data, a register key for registering the screen inputted data, an order key for switching the screen to the order screen, a clear key, a page specification key, and an end key for ending a registration. These screen keys are selected by using the function keys on the keyboard of the terminal computer 11, for instance. The color of the lens is specified in section 61.

18

The "machining 1" to "machining 3" on the auto-entry screen are for inputting general machining instructions. Various lens machining instructions can be inputted, such as lens center thickness, edge thickness, prism, decentration, outside diameter, and lens front curve (base curve).

Depending on where the beveling will be performed along the lens edge, the beveling mode can be "1:1," "1:2,"

"conform to convexity," "conform to frame," or "auto-beveling." One of these is selected and inputted. "Conform to convexity" is a mode in which the beveling is performed along the lens surface (front side).

5 Inputting the bevel position is only effective when the beveling mode is "conform to convexity," "conform to frame," or "auto-beveling." The user specifies how far back the bottom of the beveling surface is to be located from the front side of the lens, and specifies this in 0.5 mm units.

10 Even if the frame is thick and there is considerable distance from the front of the frame to the bevel groove, inputting this bevel position allows the bevel vertex to be positioned so that the front of the lens will follow along the front of the frame.

15 The bevel form can be selected from among "standard bevel," "combination bevel" (beveling for combination frames), "grooved," and "flat." A "combination bevel" is specified when decorative pieces are provided to the frame, so that the lens will not hit these decorative pieces.

20 "Grooved" or "flat" is specified in section 70.

 The manufacturer-side computer 2 receives customer information pertaining to an order (such as prescription values) from the order-side computer 11, lenses, etc., are manufactured according to the order, and these lenses are

25 assembled into spectacles and supplied to the customer. This ordering data and machining data are also included in the customer database.

While not depicted, this manufacturer-side computer 2 is also connected to machining or measurement apparatus in the factory, or to a stock control system, accounting control system, ordering system, or any of various other systems required for taking and placing orders.

As shown in Fig. 3, the manufacturer-side computer 2 has an input/output unit 21, an arithmetic and control unit 22, a database 23, and so forth. The input/output unit 21 is equipped, for example, with input means comprising a keyboard, a mouse, a floppy disk (FD), a CD-R, etc., and output means comprising a display, a printer, etc. The arithmetic and control unit 22 comprises a CPU, ROM, RAM, etc., and in addition to standard control programs found on ordinary computers, a lens design program, lens machining program, special control program, and so forth are installed.

The lens design program includes an optical design program for calculating the curve of the lens surface, lens thickness, and so forth while accessing the database 23, an optical performance comparison program for determining and comparing the optical performance for astigmatism, a base curve adjustment program, a lens weight calculation program, and other programs needed for lens design.

The lens machining program includes programs for producing machining data by compiling the data required for lens machining, such as lens refractive surface shape, lens edge shape, and beveling form, while accessing the database 23.

The special control program includes a customer database read/write program and data verification program for accesses a customer data file or the like and executing data reading, verification, storage (including temporary storage), writing, update, new addition, and so forth, or a graphic display program for lens shape and lens thickness comparison tables, for instance. The database 23 holds a customer database, lens design tables (lens data tables), lens machining tables, and so forth.

Fig. 4 illustrates an example of part of the contents of a customer database, and shows the format displayed on the display screen. The example shown in Fig. 4 (a) is a table listing personal data such as customer ID, sex, name, telephone number, address, date of birth, age, occupation, hobbies, ordering lab, order date, the name of the office placing the order, office address, and office telephone number. The example shown in Fig. 4 (b) is a "first-time prescription registration," consisting of a table listing prescription information when a specific customer places an order for the first time, and a table listing data such as the type of condition (such as myopia or astigmatism), symptoms (primary complaint), intended use, number of orders, lens prescription values, and frame prescription. SPH stands for spherical diopter, CYL stands for cylindrical diopter, AXS stands for cylindrical axis, ADD stands for addition, PD stands for distance between pupils, VA stands for naked eye visual acuity, R stands for the right eye, and

L stands for the left eye. When the same customer places an order for the second time, a "second-time prescription registration" is produced and put in the customer's file.

Fig. 5 is a flow chart of the processing involved in taking an order. An example of the processing from the placing of an order for spectacle lenses up to their supply, by means of a spectacle lens supply system having the structure discussed above, will now be described through reference to Fig. 5.

10

Placing an order

A patient receives an eye examination at an optometrist's or ophthalmologist's office, and takes the prescription to an optician office A, for example. At the optician office A, the customer's information, prescription values, and so forth are inputted according to the instruction screen on an order-side computer 11 installed at the office, and the customer's frame specifications, spectacle machining specifications, and other such information necessary for ordering spectacle lenses is determined. The order screen of the order-side computer 11 (the auto-entry screen in Fig. 2) is then used to access the manufacturer-side computer 2 via the Internet, the customer's order information, such as prescription values and various specifications, are sent, and the order is processed.

Inquiry to the customer database

Order processing commences when order access occurs from the order-side computer 11, etc. First, an inquiry is made as to whether the customer database contains an
 5 existing data file for the customer in question.

Comparison of new and old prescription values

If there is existing (old) data (that is, past data), then it is called up as a result of the above-mentioned
 10 inquiry. Otherwise, binocular vision balance design, base curve comparison, and optical performance comparison are performed, new design data accomplished the new prescription values is produced and newly registered in a file, and the procedure moves on to lens machining and so forth. How the
 15 new design data is produced will be discussed below.

If there is existing (old) data (that is, past data), the lens prescription values contained in the called-up old data (that is, the old prescription values) are compared with the lens prescription values contained in the new data
 20 sent in the course of a new order (that is, the new prescription values). A decision is then made as to whether the difference between the old and new prescription values is within a specific range. Specifically, it is decided, for instance, whether the difference in diopter is over 0.5
 25 D.

The lens prescription values referred to here include the spherical diopter (abbreviated as SPH), the cylindrical

diopter (CYL), the cylindrical axis (AXS), and the addition (ADD).

Selecting lens design data for new prescription values

5 If it is decided that the difference between the old and new prescription values is within the specified range, new design data based directly on the new prescription is usually read out from the lens design data table, additions or other update registration process necessary for the file
10 is performed, and the procedure then moves on to lens machining. Specifically, the step of comparing the optical performance and redoing the design on the basis of this comparison (adjusting optical performance), which will be discussed below, is omitted.

15 However, the optical performance adjustment discussed below (including curve matching; that is, comparison and redesign of optical performance) may still be performed after the new design data has been selected even if the difference between the old and new prescription values is
20 within the specified range. In this case, as long as the new and old prescription values (such as diopter) are within the specified range, whether or not the optical performance is adjusted will usually end up having substantially no effect on lens design, so this adjustment may be skipped.

25 On the other hand, the above-mentioned step of adjusting optical performance is performed if the difference

between the old and new prescription values is over the specified range.

Comparison of optical performance for old and new lenses

5 Next, the optical performance of the new lenses designed using this new design data is determined, and the new lens optical performance is compared to the optical performance of the old lenses. "Optical performance" as used here refers to astigmatism, curvature of field,
10 distortion, etc.

 If, as a result of this comparison of the optical performance of the old and new lenses, the difference in optical performance is within the specified range, that design data is employed, file update registration and so
15 forth are performed, and the procedure moves to lens machining.

 On the other hand, if the comparison of the optical performance of the new and old lenses indicates that the difference in optical performance exceeds the specified
20 range, then other new design data accomplished the new prescription values is selected or produced again, and the same processing is repeated until the difference in optical performance falls within the specified range.

 "Specified range" as used here means that as a result
25 of comparing the optical performance, the optical performance difference is within a range such that the customer will experience substantially no discomfort

originating in an optical performance difference when changing from old to new lenses. These ranges are empirically determined according to astigmatism, curvature of field, distortion, and so on.

5 The above is a summary of the spectacle lens supply system pertaining to an embodiment, and the following are specific examples of how to select or product the lens design data so that the optical performance will fall within the specified range (this is called optical design). These
10 examples involve design in which the object point is infinity.

How to select or produce lens design data

First, an example of a negative lens will be described.
15 Let us assume, for instance, that the previous prescription (old prescription; old lenses) was for a spherical diopter of -2 D, while the current prescription (new prescription; new lenses) is for -4 D. Specifically, the old prescription was for -2 D for both the left and right eyes, while the new
20 prescription is for -4 D for both the left and right eyes due to a change in visual acuity.

Once the step of design data selection for the new prescription values is reached, the lens design program is started, and the lens design table (lens data table) for
25 spherical design, which has been produced according to various prescriptions, is read out from the database 23. Figs. 6 and 7 are design tables (lens data tables) for

lenses with -2.0 D and -4.0 D spherical design. The refractive index of the lenses is 1.50. Figs. 8 and 9 are astigmatism diagrams for new and old lenses design using the values from the above tables. The vertical axis in these
5 drawings is the angle of the field of vision (units: degrees), while the horizontal axis is the astigmatism based on the refractive power on the optical axis (units: D, the difference (m-s) between the meridional direction (m) and the sagittal direction (s)).

10 It can be seen from Figs. 8 and 9 that the astigmatism of the new lenses (of the new design) is worse than that of the old lenses. When the astigmatism is worse, there is a higher probability that the customer will experience discomfort. Worsening of astigmatism around the periphery
15 of the field of vision when the customer changes spectacles is believed to be a particular cause of such discomfort.

In view of this, in this embodiment, astigmatism is improved by changing the first surface of the -4 D lens, which has a spherical design, to an aspherical surface by
20 the method described below. Fig. 10 is an astigmatism diagram of a new lens obtained by aspherical design. In this aspherical design, though, there is no change to the radius of curvature at the vertex. As can be seen from Figs. 9 and 10, astigmatism is improved by changing the first
25 surface to an aspherical surface, and the optical performance is the same as that shown in Fig. 8, which is a -2 D astigmatism diagram.

Spencer's formula given below (for details, see J. Opt. Soc. Am., 52 (1962), 672) is used for the design formula for determining the curved surface of the lens.

power of the first refractive surface and the second refractive surface (surface refractive power) is defined by the following formula, which includes the curvature ρ of this surface (units of 1/m, radius of curvature $R = 1/\rho$) and
 5 the refractive index n of the lens material.

$$\text{Surface refractive power} = (n - 1) \times \rho = (n - 1)/R \quad (1)$$

The refractive power of the first refractive surface of
 10 a spectacle lens is called the base curve.

The curve of lens at an aspherical surface is calculated using the radius of curvature at the vertex.

Example of when the prescription is different for the left
 15 and right eyes

Next we will describe an example of when the previous (old) prescription (old lens) was -2 D for both the left and right and eyes, but the current (new) prescription is -2 D for the left eye and -4 D for the right eye. In other words,
 20 this is a case in which myopia is more advanced in the right eye for one reason or another.

Just as in the case discussed above, the lens design program reads a lens design table (lens data table) for spherical design, which has been produced according to
 25 various prescriptions. Figs. 12 and 13 illustrate examples of design tables (lens data table) for lenses with spherical

design of -2.0 D for the left eye and -4.0 D for the right eye, respectively. The refractive index of the lenses is 1.50.

Figs. 14 and 15 are astigmatism diagrams for lenses designed using the values in the tables in Figs. 12 and 13. The vertical axis in these drawings is the angle of the field of vision (units: degrees), while the horizontal axis is the astigmatism based on the refractive power on the optical axis (units: D, the difference (m-s) between the meridional direction (m) and the sagittal direction (s)). It can be seen from these tables the optical performance is worse for the lens for the right eye, in which myopia is more advanced. This is what causes discomfort when the user changes spectacles.

The use of a curve (surface refractive power) along with the radius of curvature is a well known concept when expressing the shape of a spectacle lens. This curve is calculated from the above formula (1). In Formula 1, R is the radius of curvature, in units of m (meters), and n is the refractive index of the lens. Calculating the curve for the first surfaces (first refractive surfaces) using Formula 1 yields values of 3.99 D and 2.99 D, respectively. In this example, the curve difference at the first surfaces (first refractive surfaces) is 1 D between the lenses of the new and old prescriptions.

Thus, when the prescription is different for the left and right eyes, the base curves are generally also different.

The spectacles will look odd if the difference is too pronounced (over 1 D). When myopia is more advanced in one eye, as in this example, not only will the optical performance suffer as mentioned above, but the aesthetic appearance of the spectacles will also suffer. In view of this, the base curves of the left and right lens are matched and the optical performance is made the same as with the previous prescription.

10 How to design matching base curves

First of all, to eliminate the curve difference, the curved surface shape of the first and second refractive surfaces is determined so as to satisfy the following conditions for the lens on the -4.0 D side.

- 15 (a) The design standard should be an aspherical design with an approximated curve on the first refractive surface.
- (b) Astigmatism performance should not be compromised as an aspect of optical performance.

The above-mentioned method utilizing ray tracing and Spencer's formula is employed as the method for determining a curved surface having a curvature that satisfies the above conditions. This method was described in detail above.

Fig. 16 is a table listing the radius of curvature and so forth for a new prescription lens obtained by redesign (aspherical design -4.0 D). The refractive index of the lens is 1.50. In this table, the first surface (which is an

aspherical surface) radius of curvature indicates the radius of curvature at the vertex of the first surface.

It is clear from this table that an aspherical design is used for the lens shape on the first surface (first
5 refractive surface) of this new design lens, resulting in 125.647 mm (3.98 D), and the lens curve difference has also been corrected to within 1 D. Fig. 17 is an astigmatism diagram for a new prescription lens obtained by new design. As is clear from Figs. 14 and 17, the optical performance is
10 maintained substantially the same as that before redesign, while the appearance of the spectacles is markedly improved.

As in this example, it is possible to design lenses such that the base curves of the left and right lenses are matched, which maintains the good appearance of the
15 spectacles while the optical performance is kept the same as that obtained with the previous prescription. This means that the wearer will experience no discomfort upon changing spectacles, but at the same time the spectacles will retain their good appearance.

20 The astigmatism was kept the same in the above example, but it is only necessary for one or more of astigmatism, curvature of field, and distortion to be kept substantially the same. Of the five Seidel aberrations in spectacle lenses, it can be seen that, except in the case of lenses
25 with very high refractive power (diopter), there is no need to factor in spherical aberration or coma aberration because the pupil diameter is smaller than the spectacle lens and

20 New design: When the same customer data does not exist in
the customer database on the manufacturer-side computer

35

As mentioned previously, the curvature of the first surface (object side) is different when the prescriptions for the left and right eyes are different. If we look at this in terms of the appearance (aesthetics) of the spectacles, it has been found that there will be a noticeable difference in the appearance of the left and right lenses, giving an unbalanced look, if the curve difference between the left and right lenses is over about 1 D, although this varies somewhat with personal taste. In view of this, in this embodiment, a curve difference over this is considered to result in an imbalance between the left and right lenses, so a redesign program is executed.

For instance, let us assume that the prescription is -1 D for the left eye and -3 D for the right eye. With an existing lens design program, a design table for lenses of spherical designs that have been produced ahead of time according to prescriptions is selected, and the values in this table are used in the design. Fig. 18 illustrates an example of a design table for lenses with a spherical design. The refractive index of the lens is 1.50. Figs. 20 and 21 are astigmatism diagrams of lenses produced using the design values in the table of Fig. 18. It can be seen from these graphs that astigmatism is favorably corrected.

Fig. 22 is an astigmatism diagram for the lens (right) obtained by redesign. As is clear from Fig. 22, the optical performance is substantially the same as or better than that prior to redesign, while the aesthetic appearance is markedly improved.

25 Fig. 23 is an example of a design table (lens data
table) for lenses of spherical design. The overall height

in the table refers to the height of the entire lens when the lens is viewed from the side in a plane.

Figs. 24 (a) and (b) are astigmatism diagrams of the left and right lenses designed using the values in the above table, respectively. The vertical axis in these drawings is the angle of the field of vision (units: degrees), while the horizontal axis is the astigmatism based on the refractive power on the optical axis (units: D, the difference (m-s) between the meridional direction (m) and the sagittal direction (s)). It can be seen from these graphs that good optical correction is achieved.

Calculating the curve for the first surfaces (first refractive surfaces) using Formula 1 yields values of 5.46 D and 8.05 D, respectively. In this example, the curve difference at the first surfaces (first refractive surfaces) is 2.59 D between the lenses of the left and right lenses. Fig. 25 is a table listing the radius of curvature, etc., of a lens (right) obtained by redesign. In the table, the first surface (which is an aspherical surface) radius of curvature indicates the radius of curvature at the vertex of the first surface. It is clear from this table that by using an aspherical design for the lens shape on the first surfaces (first refractive surfaces) of these redesigned lenses results in 92.242 mm (5.42 D), and the lens curve difference has also been corrected to within 1 D. Fig. 26 is an astigmatism diagram for a lens (right) obtained by redesign. As is clear from Fig. 26, the optical performance

is maintained substantially the same as that before redesign, while the appearance of the spectacles is markedly improved. Fig. 27 consists of diagrams illustrating a screen display comparing the curved surface shape of a lens before and
 5 after redesign. It can be seen from Fig. 27 that the curvature of the first surface (first refractive surface) is substantially the same on the left and right as a result of redesign. The base curves of the left and right lenses were adjusted to the shallower curve, but the shallower curve
 10 does not necessarily have to be used as the standard, and adjusting to the deeper curve is also possible.

If we consider the shape of the above-mentioned Tscherning's ellipse, which exhibits the optimal base curve in a spectacle lens, we see that with a lens having a
 15 negative diopter, the curvature of the base curve tends to become flatter as the diopter of the lens increases. On the other hand, with a lens having a positive diopter, the curvature of the base curve tends to become steadily steeper as the diopter of the lens increases. This is because, as
 20 seen with the slope of Tscherning's ellipse, the slope steadily flattens out with a negative lens, while the slope steadily steepens with a positive lens.

Therefore, in implementing the present invention, it is preferable if the difference in the diopter between the left
 25 and right eyes is at least 0.5 D in a prescription including a positive diopter, if the difference in diopter between the left and right eyes is at least 1 D in a prescription

Also, in the above example, the lens data table was prepared for prescription lenses with new and old spherical designs, but the lens data table may instead be for aspherical designs. Also, the lens data table in the above example was prepared for left and right single vision lenses, but this lens data table may instead be for multifocal lenses or progressive-power lenses. That is, it is also possible to match the curves of the far portions (the portions used for far vision) and make the optical performance the same.

As discussed above, when lens design data is selected
25 and data including this selected design data is updated or
newly registered, the procedure moves on to the lens
machining step. This lens machining step consists of

selecting or calculating machining data based on lens design data and so forth, coordinate conversion, determination of the machining start point and machining axis, confirmation calculation of the edge thickness prior to lens machining, 5 machining the lens refractive surface, edging the lens to the frame shape, beveling the edge of the lens, and other such processing. These are carried out by sending machining-related data to the control computers of the various machining devices of the factory which are connected 10 to the manufacturer-side computer 2.

The machined lenses are sent to an optician, optometrist, etc., through a delivery system, accounting system, and so forth. Spectacles are produced in this way. The spectacles thus produced are delivered to the customer 15 via the optician, optometrist, etc. The newly updated or registered database will be useful for the next order. As shown in Fig. 27, data such as optical performance, the lens center thickness, edge thickness, overall height, or weight, or cross sections of the lens, may be transmitted to the 20 order-side computer as desired by the ordering side. In particular, data based on previous prescription values or lens data, such as optical performance, the lens center thickness, edge thickness, overall height, or weight, or cross sections of the lens, can be compared with the current 25 data.

With the spectacle lens supply system pertaining to the above embodiment, the effective use of a customer database

makes it possible to supply customers with spectacle lenses
 that are exactly suited to their needs. Also, since the
 customer database can be used like an electronic medical
 chart by updating it every time an order is received, the
 5 history of prescription values for a customer can be
 reviewed, which is useful for medical purposes. Furthermore,
 since the optical performance is examined and optical design
 is performed as needed every time an order is received,
 spectacle lenses having the optical performance best suited
 10 to the customer can always be provided. Also, orders for
 just one lens are sometimes placed by customers who have
 lost or damaged either the left or right lens, in which case
 this system can be applied and its advantages fully
 exploited as long as the optical performance of the
 15 remaining lens is known.

In this example, the network system involved connecting
 the manufacturer-side computer and the order-side computer
 via the Internet, but a dedicated line or the like can be
 used instead of the Internet. Furthermore, the network
 20 linking the manufacturer-side computer and the order-side
 computer need not do so directly, and of course may link
 them indirectly by having a server in between, or by
 interposing a plurality of manufacturer-side computers from
 a server, for example, or a plurality of units may be
 25 combined.

INDUSTRIAL APPLICABILITY

